

## IN THE CLAIMS

Claims 1-23 (Canceled)

Claims 24-32 (Canceled)

33. (Currently Amended) The magnetic recording disk of claim ~~34~~ 31, wherein the third zone is a load/unload zone.

34. (Currently Amended) ~~The magnetic recording disk of claim 31~~ A magnetic recording disk, comprising:  
a first zone to store data;  
a second zone adjacent to the first zone, the second zone having a surface to increase a fly height of a head greater than when the head is operating over the first zone;  
and  
a third zone adjacent to the second zone in which to park the head thereabove,  
wherein the first zone comprises a discrete track recording (DTR) pattern.

35. (Original) The magnetic recording disk of claim 34, wherein the second zone has a planar surface relative to the DTR patterned surface of the first zone.

36. (Original) The magnetic recording disk of claim 35, wherein the planar surface of the second zone is substantially smooth.

37. (Original) The magnetic recording disk of claim 35, wherein the planar surface has a texture.

38. (Original) The magnetic recording disk of claim 35, wherein the planar surface of the transition zone has a texture produced through the deposition of a plurality of layers of the disk above a textured layer.

40. (Original) The magnetic recording disk of claim 38, wherein the textured layer is a textured substrate.

41. (Original) The magnetic recording disk of claim 38, wherein the textured layer is textured NiP layer.

42. (Canceled)

43. (Canceled) A disk drive, comprising:

a slider comprising a Hall effect head or a head having a magneto-resistance read element; and

a magnetic recording disk comprising:

a first zone to store data;

a second zone adjacent to the first zone, the second zone having a surface to increase a fly height of the slider greater than when the slider is operated over the first zone; and

a third zone adjacent to the second zone in which to park the slider thereabove.

44. (Canceled)

45. (Currently Amended) The disk drive of claim ~~46~~ 43, wherein the third zone is a load/unload zone and wherein the slider is coupled to a suspension arm, the suspension arm configured to park the slider above the load/unload zone when the slider resides on a ramp.

46. (Currently Amended) ~~The disk drive of claim 43~~ A disk drive, comprising:  
a slider comprising a Hall effect head or a head having a magneto-resistance read  
element; and  
a magnetic recording disk comprising:  
a first zone to store data;  
a second zone adjacent to the first zone, the second zone having a surface to  
increase a fly height of the slider greater than when the slider is operated over the  
first zone; and  
a third zone adjacent to the second zone in which to park the slider  
thereabove, wherein the first zone comprises a discrete track recording pattern.

47. (Original) The disk drive of claim 46, wherein the second zone has a planar surface relative to the discrete track recording pattern of the first zone.

Claims 48 -51 (Canceled)

52. (Original) The disk drive of claim 47, wherein the planar surface of the second zone has a texture produced through the deposition of a plurality of layers of the disk above a textured layer.

53. (Original) The disk drive of claim 52, wherein the textured layer is a textured substrate.

54. (Original) The disk drive of claim 52, wherein the textured layer is a textured NiP layer.

55. (Canceled)

56. (Currently Amended) The disk drive of claim ~~46~~ 43, wherein the slider further comprises a body having a first width and an air bearing having a second width, wherein the second zone has a third width being wider than the second width of the air bearing and narrower than the first width of the slider body.

57. (Canceled)

58. (Original) A load/unload disk drive, comprising:  
a slider comprising a Hall effect head or a head having a magneto-resistance read element;  
a ramp; and

a magnetic recording disk, wherein the ramp is disposed above a first portion of the magnetic recording disk, and wherein the magnetic recording disk comprises:

a data zone having a discrete track recording pattern; and

a load/unload zone adjacent to the data zone, wherein the load/unload zone includes the first portion residing beneath the ramp and a second portion extending beyond the ramp, the second portion of the load/unload zone having a surface to increase a fly height of a slider greater than when the slider is operating over the data zone.

59. (Original) The load/unload disk drive of claim 58, wherein the second portion of the load/unload zone has a planar surface relative to the discrete track recording pattern of the data zone.

60. (Original) The load/unload disk drive of claim 59, wherein the planar surface of the load/unload zone is substantially smooth.

61. (Original) The load/unload disk drive of claim 59, wherein the planar surface has a texture.

62. (Original) The load/unload disk drive of claim 59, wherein the planar surface of the load/unload zone has a texture produced through the deposition of a plurality of layers of the magnetic recording disk above a textured layer.

63. (Original) The load/unload disk drive of claim 62, wherein the textured layer is a textured substrate.

64. (Original) The load/unload disk drive of claim 62, wherein the textured layer is a textured NiP layer.